



TAHITI

VENTILATED PELLET STOVE



ECO
DESIGN
2022

TAHITI

TAHITI		12C
ENERGY CLASS		
DIMENSIONS (LxPxH)	cm	49,6x56,1x103
WEIGHT	kg	112
NOMINAL INPUT (min.-max.)	kW	4,87 - 13,22
NOMINAL OUTPUT (min.-max.)	kW	4,53 - 11,52
EFFICIENCY AT NOMINAL OUTPUT (min.-max.)	%	93,07 - 87,15
MINIMUM DRAUGHT AT THE CHIMNEY BASE	Pa	12
SMOKE OUTLET Ø	mm Ø	80
AIR DUCT DIAMETER	mm Ø	40
PELLET RESERVOIR CONTENT	kg	20
AVERAGE CONSUMPTION (min.-max.)	kg/h	1 - 2,73
Nominal ELECTRIC ABSORPTION	W	146
ELECTRIC ABSORPTION at the ignition stage	W	363
HEATING VOLUME	m ³	129 ÷ 330

PLUS PRODUCT



VENTILATED
STOVE



CERAMIC
GLASS



CAST IRON
BRAZIER



DAILY / WEEKLY
PROGRAMMING



POWER
MODULATION



REAR SMOKE
OUTLET



DUCTABLE
(optional)



WI-FI
(optional)



Black



White



Burgundy



Download on the
App Store

GET IT ON
Google Play