



YURA

YURA

VENTILATED PELLET HYDRO-STOVE



ECO
DESIGN
2022

YURA		14	18	22	26	30
ENERGY CLASS		A+	A+	A+	A+	A+
DIMENSIONS (LxPxH)	cm	46x48x95	55x59x111	59x68x122	70x74x137	70x74x137
WEIGHT	kg	145	160	230	280	280
NOMINAL INPUT (min.-max.)	kW	5,23 - 14,79	4,1 - 18	5,26 - 23,12	8,95 - 27,34	8,95 - 32,41
NOMINAL OUTPUT (min.-max.)	kW	5,04 - 13,84	4 - 17,14	5,08 - 21,96	8,57 - 25,86	8,57 - 30,48
OUTPUT TO THE WATER (min.-max.)	kW	3,81 - 10,53	3,10 - 13,43	4,20 - 17,86	6,51 - 20,35	6,51 - 24,38
OUTPUT TO THE ROOM (min.-max.)	kW	1,22 - 3,31	0,9 - 3,7	0,88 - 4,10	2,06 - 5,51	2,06 - 6,1
EXCHANGER WATER CONTENT	l	17	31	50	60	60
EXPANSION VESSEL CAPACITY	l	6	7	8	8	8
MAXIMUM WORKING PRESSURE	bar	3	3	3	3	3
MANOMETRIC HEAD OF THE PUMP	m	6	6	6	6	6
WATER SIDE PRESSURE DROP (Δt 10 K) / (Δt 20 K)	mbar	-	181 / 45,2	186,8 / 46,7	285,9 / 71,5	405 / 101,2
EFFICIENCY AT NOMINAL OUTPUT (min.-max.)	%	93,54 - 96,29	97,54 - 94,97	95,74 - 96,71	95,79 - 94,56	95,79 - 94,03
MINIMUM DRAUGHT AT THE CHIMNEY BASE	Pa	12	8	10	6	6
SMOKE OUTLET \varnothing	mm \varnothing	80	80	80	100	100
AIR INTAKE DIAMETER	mm \varnothing	50	50	50	50	50
PELLET RESERVOIR CONTENT	kg	17	33	38	57	57
AVERAGE CONSUMPTION (min.-max.)	kg/h	1,067 - 3,017	0,84 - 3,7	1,113 - 4,893	1,8 - 5,5	1,8 - 6,3
ELECTRIC ABSORPTION (nominal / at ignition stage)	W	82 - 350	82 - 350	145 - 400	165 - 430	165 - 430
HEATING VOLUME	m ³	340	420	510	600	730
NOISINESS	dB	35 / 45	35 / 50	35 / 50	35 / 50	35 / 50

PLUS PRODUCT



HYDRO
VENTILATED



HYDRO
(mod. 14)



STEEL
BRAZIER
(mod. 14)



CAST IRON
BRAZIER



MAGIC
GLASS



REAR SMOKE
OUTLET



POWER
MODULATION



WEEKLY
PROGRAMMING



WI-FI
(optional)



Black



White



Burgundy



Download on the
App Store

GET IT ON
Google Play